

DANI ALONSO OPTICAL CONNECTIVITY

High-density integrated energy cabinet 47U available now



Overview

47U Premium Server Cabinet 800mm/31.5in wide and offer various depth options. Industry Standards: EIA 310 Features Static load: 1000kg. The 19inches server cabinet features 80% perforated front and double rear doors for optimal airflow, supports up to 1500kg static load, and offers modular design for efficient cable management and accessibility. This enclosure provides flexible ways to mount your devices reliably and securely. With vented doors, built-in cable and. Our flagship Environ SR600 47u racks are designed for high-density server and equipment setups. With a load capacity of up to 1500kg, they come in a width of 600 mm. Available in Black or Grey/White, these racks feature 70% ventilated mesh doors, split side panels, adjustable 19" profiles with U. IP Rated Outdoor FM Cabinet offer protection against the unauthorized access, physical impacts (vandalism), Water/Dust ingress in according to EN60529 standard, as well as industrial environmental challenges including high temperatures. Cabinets are available with integrated thermal management. The Prism FI is an innovative enclosure constructed from an extruded aluminium platform, with a high perforation rate for maximum airflow. The new 83% increased airflow mesh system exceeds all of the major manufacturer's requirements which ensure the FI range is fit for all installations.



Article Content

Equip Dynamic Flex 19" Free Standing Server Cabinet, 47U,

Introducing the "Dynamic Flex Line" Cabinets: Designed for user-friendly installation of active and passive network components, these cabinets prioritize efficient cable management.

Contact Us

Continue your research online:

Website: <https://danialonso.es>

Technical inquiry: <https://danialonso.es/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

